

ILT CaseLight

LED Refrigerated Case Lighting System

Make Your Prepared Foods POP With CaseLight™ LED Modules!

- **Easily Replace Existing Cooler/Freezer Display Case Fluorescent Lights**
- **Easy Mounting Using TEK Screws or VHB Foam Tape When Space is Limited**
 - **No Need to Empty Shelves!**
- **Lower Energy Bills and No Burned Out Bulbs!**
- **Long Fixture Life - YEARS vs. Weeks/Months**
- **Low Maintenance-5 Year Warranty on CaseLight Modules & Power Supplies**
- **CaseLight Modules Made in the USA**

Improving on the success of ILT's previous CaseLight modules for refrigerated/freezer display cases, ILT's new, more efficient CaseLight module has even lower power consumption and higher overall optical performance for your reach-in coolers and freezers. For Retrofit or New cases, ILT CaseLight can be installed easily and cost-effectively.

LED-based CaseLight modules provide all of the advantages of LED-based lighting including much longer life, much lower energy consumption and much better lighting characteristics.

Brighter light focused on the merchandise!

**Over 55 YEARS of ILT Lighting Experience
Goes Into Every CaseLight**

ILT INNOVATIONS



Model Number Key

	Length	Finish	Color/CCT	Configuration
Typical Model Number	ILT48 -	BAO -	W40	CE
Options	48 (48")	BAO (Brite Anodized)	35 (3500K)	LE (Left End, External Power Supply)
	60 (60")	BAO	40 (4000K)	RE (Right End, External Power Supply)
	70 (70")	BAO	50 (5000K)	CE (Center, External Power Supply)

Technical Specifications

Model Number	Description	Lumens	Energy (Watts)	Lumens/Watt	CRI (Typical)
ILT48-BAO-W__CE	48", Brite Anodized, Center unit	1,385	14.8	93.6	82
ILT48-BAO-W__LE	48", Brite Anodized, Left unit	693	7.4	93.6	82
ILT48-BAO__RE	48", Brite Anodized, Right unit	693	7.4	93.6	82
ILT60-BAO-W__CE	60", Brite Anodized, Center unit	1,853	19.8	93.6	82
ILT60-BAO-W__LE	60", Brite Anodized, Left unit	927	9.9	93.6	82
ILT60-BAO-W__RE	60", Brite Anodized, Right unit	927	9.9	93.6	82
ILT70-BAO-W__CE	70", Brite Anodized, Center unit	2,312	24.7	93.6	82
ILT70-BAO-W__LE	70", Brite Anodized, Left unit	1,161	12.4	93.6	82
ILT70-BAO-W__RE	70", Brite Anodized, Right unit	1,161	12.4	93.6	82

L70 data for the ILT CaseLight fixture is greater than 50,000 hours for lumen maintenance. TM-21 calculations show L70 lumen maintenance data will exceed 78,000 hours. Please contact ILT for a copy of the TM-21 report.

Rev. E (Nov 2021)



10 Technology Drive, Peabody, MA 01960
978-818-6180 978-818-6181 fax
www.intl-lighttech.com



Specifications subject to change without notice.

