

POWER FLEX ACCENT/COVE LIGHTING

APPLICATION:

- Back lighting panel
- Edge lighting for a variety of objects
- Cove lighting
- Indirect accent decorative lighting in commercial and residential applications
- Signage applications
- Ideal for architectural and landscape lighting



GTL-PFLEX-48

FEATURES:

- Adopt 0.5W SMD LED
- White available in warmer colors 3000k
- Flexible circuit board with 3M self-adhesive backing for easy install
- Available in 5 meter and 10 meter reels
- Available in warm whites of 4800K and 3000K

Specifications:

Part No.	Operating Voltage (V)	Current (mA)	Power dissipation (W)	Emitting color	Peak wavelength (nm)	Viewing Angle	Luminous flux (lm)		LED quantity (pc)	Housing Material
							min	max		
GTL-PFLEX-48-R	12	1200	24	Red	626	140	288	384	48	FPG or FR-4, PVC
GTL-PFLEX-48-Y	12	1200	24	Yellow	590	140	288	384	48	FPG or FR-4, PVC
GTL-PFLEX-48-B	12	1200	24	Blue	470	140	144	192	48	FPG or FR-4, PVC
GTL-PFLEX-48-G	12	1200	24	Green	525	140	384	480	48	FPG or FR-4, PVC
GTL-PFLEX-48-W-6000k	12	1200	24	White	6000k	140	480	580	48	FPG or FR-4, PVC

GTL-PFLEX-48 Mechanical Detail

