

WATERPROOF FLEX 60 ACCENT/COVE LIGHTING

APPLICATION:

- Back lighting panel
- Edge lighting for a variety of objects
- Cove lighting
- Indirect accent decorative lighting in commercial and residential applications
- Signage applications
- Ideal for architectural and landscape lighting



Feature:

GTL-FLEX-SL60-W-60

- Makes use of 2.5mm height SMD LED witch can be used in small areas
- Waterproof rating of IP 67
- Flexible circuit board come with external mounting clips for easy install
- Available in 5 meter reels
- Easy two prong connectors provided on each end of circuit
- Can be customized according to specifications, up to 5 meters
- 3M self adhesive backing on special order
- Custom color temperature available call for details

Specifications:

Part No.	Operating Voltage (V)	Current (mA)	Power dissipation (W)	Emitting color	Peak wavelength (nm)	Viewing Angle	Luminous flux		LED quantity (pc)	Measure LxW (mm)
							(lm)			
							min	max		
GTL-FLEX-SL60-R	12	400	4.8	Red	626	140	42	60	60	40"x0.31"x.066"
GTL-FLEX-SL60-Y	12	400	4.8	Yellow	590	140	42	60	60	40"x0.31"x.066"
GTL-FLEX-SL60-B	12	400	4.8	Blue	470	140	30	36	60	40"x0.31"x.066"
GTL-FLEX-SL60-G	12	400	4.8	Green	525	140	72	96	60	40"x0.31"x.066"
GTL-FLEX-SL60-W-30	12	400	4.8	Warm White	3000k	140	84	104	60	40"x0.31"x.066"
GTL-FLEX-SL60-W-60	12	400	4.8	White	6000k	140	84	104	60	40"x0.31"x.066"

GTL-FLEX-SL60, Mechanical Detail

