

ILT-FLX350-OS Edge Lighting for Acrylic

APPLICATION:

- Edge lighting for Acrylic
- Snap Poster frames
- POP displays
- Signage applications
- Back lighting panel
- Shallow sign illumination
- Edge lighting for various commercial applications



FEATURES:

- .25" wide flexible PCB for narrow applications
- Flexible circuit board with 3M self-adhesive backing for easy install
- Available in 16 foot reels
- Available in two white color temperatures.

Specifications

Part No.	Operating Voltage	Power dissipation / ft	Emitting color	Peak wavelength	CRI (Color rendering index)	Viewing Angle	Luminous flux / ft		LED quantity / ft	Measure
	(V)	(W)		(nm)			(lm)		(pc)	LxW
							min	max		(in)
ILT-FLX350-OS40	24	9.5	White	4000k	85	120	800	825	21	11.55" x .25"
ILT-FLX350-OS50	24	9.5	White	5000k	85	120	840	865	21	11.55" x .25"

ILT-FLX350-OS Mechanical Detail



ILT-FLX-350-OS50

Sold in 16 foot reels
50 segments of 3.85"

For more information
please contact:
Joe Reis or
Pete Couture



10 Technology Drive Peabody MA 01960
ph 978-818-6180 fax 978-818-6181
www.intl-lighttech.com